

## Universal Load Cell

### FEATURES

- Capacities 50 to 10000 kg (50 to 20k lbs)
- Nickel-plated steel construction
- Certified to NTEP class III 3000d and class IIIIL 10000d
- Suitable for compression and tension applications
- Trimmed output versions available
- Sealing: IP65
- **Optional**
  - FM approved for use in potentially explosive atmospheres



### APPLICATIONS

- Suspended hoppers
- Overhead track scales
- Force measurement


### DESCRIPTION

The 363 is a multi-purpose nickel-plated S-Type load cell which can be used in tension or compression.

This product is suitable for a wide range of hybrid scales, overhead track scales, belt scales, and process weighing applications.

Reliable sealing is ensured by the proprietary TRANSEAL potting compound and additional mechanical protection of the strain gage area.

### OUTLINE DIMENSIONS in millimeters



#### Cable specifications

Cable length: 6m

|              |             |
|--------------|-------------|
| Excitation + | Red         |
| Excitation - | Black       |
| Output +     | Green       |
| Output -     | White       |
| Shield       | Transparent |

Cable screen is not connected to the load cell body.

| Cap (kg)         | 50, 100        | 250, 500       | 1000     | 2500           | 5000 | 7500           | 10000           |
|------------------|----------------|----------------|----------|----------------|------|----------------|-----------------|
| Cap (lbs)        | 50-300         | 500-1.5k       | 2k, 2.5k | 3k*, 5k        | 10k  | 15k            | 20k             |
| A                | 50.8           | 50.8           | 50.8     | 76.2           | 74.7 | 87.4           | 112.8           |
| B                | 61.0           | 61.0           | 61.0     | 99.1           | 99.1 | 139.7          | 177.8           |
| C                | 11.7           | 18.0           | 24.4     | 24.4           | 30.7 | 37.1           | 42.9            |
| D <sub>max</sub> | 16.5           | 22.9           | 29.2     | 29.2           | 35.6 | 41.4           | 47.8            |
| E (kg)           | M8x1.25 - 6H   | M12x1.75 - 6H  |          | M20x1.5 - 6H   |      | M24x2 - 6H     | M30x2 - 6H      |
| E (lbs)          | ¼ - 28UNF - 2B | ½ - 20UNF - 2B |          | ¾ - 16UNF - 2B |      | 1 - 14UNS - 2B | 1¼ - 12UNF - 2B |
| F                | 30.5           | 30.5           | 30.5     | 49.5           | 49.3 | 69.9           | 88.9            |
| G                | 8.9            | 8.9            | 8.9      | 14.0           | 15.7 | 22.4           | 31.8            |

## Universal Load Cell

| <b>SPECIFICATIONS</b>                       |  |              |                     |
|---|--|--------------|---------------------|
| <b>PARAMETER</b>                            | <b>VALUE</b>   |              | <b>UNIT</b>         |
| Standard capacities (E <sub>max</sub> )     | 50, 100, 250, 500, 1000, 2500, 5000, 7500, 10000                                     |              | kg                  |
| Standard capacities (E <sub>max</sub> )     | 50, 75, 100, 150, 200, 250, 300, 500, 750, 1k, 1.5k, 2k, 2.5k, 3k, 5k, 10k, 15k, 20k |              | lbs                 |
| Accuracy class per NTEP                     | NTEP IIIIL   | Non-Approved |                     |
| Maximum no. of verification intervals (n)   | 10000  |              | mV/V                |
| Rated output—R.O.                           | 3.3±0.3  |              | mV/V                |
| Rated output—R.O. (trimmed option)          | 3.0±0.0075   |              | mV/V                |
| Zero balance                                | 1.0  |              | ±%FSO               |
| Combined error                              | 0.0200   | 0.05         | ±%FSO               |
| Non-repeatability                           | 0.0100   | 0.0200       | ±%FSO               |
| Minimum dead load output return             | 0.0500   |              | ±% applied load     |
| Creep error (30 minutes)                    | -  | 0.0600       | ±% applied load     |
| Creep error (20 minutes)                    | 0.0030   | 0.0200       | ±% applied load     |
| Temperature effect on min. dead load output | 0.0090   | 0.0250       | ±% FSO/5°C          |
| Temperature effect on sensitivity           | 0.0072   | 0.0250       | ±% applied load/5°C |
| Minimum dead load                           | 0  |              | % E <sub>max</sub>  |
| Maximum safe overload                       | 150  |              | % E <sub>max</sub>  |
| Ultimate overload                           | 300  |              | % E <sub>max</sub>  |
| Maximum safe side load                      | 100  |              | % E <sub>max</sub>  |
| Excitation, recommended                     | 10   |              | VDC or VAC RMS      |
| Excitation, maximum                         | 15   |              | VDC or VAC RMS      |
| Input impedance                             | 390±15   |              | Ω                   |
| Output impedance                            | 350±3.5  |              | Ω                   |
| Insulation resistance                       | ≥5000  |              | MΩ                  |
| Compensated temperature range               | -10 to +40   |              | °C                  |
| Operating temperature range                 | -40 to +80   |              | °C                  |
| Storage temperature range                   | -40 to +90   |              | °C                  |
| Element material                            | Nickel-plated alloy steel  |              |                     |
| Sealing                                     | IP65   |              |                     |

FSO—Full Scale Output

All specifications subject to change without notice.

## Disclaimer

ALL PRODUCTS, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE.

Vishay Precision Group, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay Precision Group"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

The product specifications do not expand or otherwise modify Vishay Precision Group's terms and conditions of purchase, including but not limited to, the warranty expressed therein.

Vishay Precision Group makes no warranty, representation or guarantee other than as set forth in the terms and conditions of purchase. **To the maximum extent permitted by applicable law, Vishay Precision Group disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.**

Information provided in datasheets and/or specifications may vary from actual results in different applications and performance may vary over time. Statements regarding the suitability of products for certain types of applications are based on Vishay Precision Group's knowledge of typical requirements that are often placed on Vishay Precision Group products. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application.

No license, express, implied, or otherwise, to any intellectual property rights is granted by this document, or by any conduct of Vishay Precision Group.

The products shown herein are not designed for use in life-saving or life-sustaining applications unless otherwise expressly indicated. Customers using or selling Vishay Precision Group products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify Vishay Precision Group for any damages arising or resulting from such use or sale. Please contact authorized Vishay Precision Group personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.